


US Series insert bearings

Insert Bearings US Series insert bearings



WUXI GUANGQIANG BEARING TRADE CO.,LTD



Model	Dimensions (mm)							Capacity (kN)			Mass
	d	D	B	d ₁	D ₁	E	r1.2	C	C ₀	P _u	kg
US 203 2S	17	40	12	24.2	32.6	3.6	0.6	7.35	4.75	0.14	0.064
US 303 2S	17	47	14	26.5	37.6	4.3	0.7	13.5	6.55	0.275	0.14
US 204 2S	20	47	14	28.2	38.6	4.3	1	12.8	6.6	0.196	0.094
US 205 2S	25	52	15	33.6	44	4.3	1	14	7.8	0.232	0.116
US 303 2S	25	62	17	36.6	50.9	5.6	1.1	22.5	11.6	0.49	0.2
US 206 2S	30	62	16	39.7	51.6	5.1	1	19.5	11.3	0.335	0.18
US 306 2S	30	72	19	44.6	59.2	6.1	1.1	28.1	16	0.67	0.3
US 207 2S	35	72	17	46.1	60.5	5.6	1.1	25.5	15.3	0.455	0.28
US 307 2S	35	80	21	49.5	66.1	7	1.5	33.2	19	0.82	0.4
US 208 2S	40	80	18	52	67.3	6.1	1.1	32.5	19.8	0.56	0.37
US 308 2S	40	90	23	56.1	74.7	7.6	1.5	41	24	1.02	0.55
US 209 2S	45	85	19	56.6	72.6	6.1	1.1	32.5	20.4	0.64	0.4
US 309 2S	45	100	25	62.1	83.7	7.7	1.5	52.7	31.5	1.34	0.73
US 210 2S	50	90	20	62.5	78.2	6.4	1.1	35	23.2	0.695	0.45
US 310 2S	50	110	27	68.7	92.6	7.7	2	61.8	38	1.6	0.95
US 211 2S	55	100	21	69.1	85.9	7	1.5	43.5	29	0.865	0.6
US 212 2S	60	110	22	75.5	95	7.7	1.5	52	36	1.06	0.77
US 213 2S	65	120	23	82.5	102.46	7.6	1.5	57	40	1.73	0.94